

MULTI PURPOSE LED RETROFIT

Model #	ODMP13113 NU	ODMP13163 NU	ODMP13193 NU	ODMP13253NU
Input Wattage	11W	16W	19W	25W
Input Voltage Range (V)	120			
Delivered Lumens (lm)	830	1250	1520	2200
Efficacy (lm/W) - 3000K	75	78	80	88
Color Rendering Index (CRI)	>82			
Color Temperature (CCT)	3000K /4000K/5000K			
Equivalent Wattage (Approx.)	2 X 9W CFL	2 X 13W CFL	2 X 18W CFL	2 X 23W CFL
Beam Angle	120°			
Power Factor	> 0.9			
MAX THD (%)	< 34			
Ambient Temp (°F)	(-4oF-110 oF) (-20oC-43oC)			
LM-79	Yes			
LM-80 (8000 hours)	Yes			
Safety	ETL/cETL			
Fixture Mounting:	Ceiling, Pendant, Portable Lamp, Torcher e (SS/PS Mounting included)			
Dimming compatible	Yes, SCR Dimming			
Compatible Dimmers	Leviton: IPI10, DVCL153P-WH, CT-600P-BL, MACL153M, CPL06-10Z			
	Lutron: 6674-P, VPM10-iL, 6672-L, 6681, CTCL-153PD, S-600P, CF1000P, CTELV-303P, LGCL-153PL, VP1-6-iL, PD-6WCL, VPM10, MACL153M			
	Cooper: DLC03P, Legrand: 341107-01/15			
	# Contact us for the latest compatible availability of the dimmer			
Diameter	ø4.13" (104mm)	ø5.7"(144mm)	ø7.2" (185mm)	
Height	1.5" (38mm)	0.78" (20mm)		
Weight: (g)		110	170	300
Life (Hours)	> 40,000 hours			
Warranty (Years)	5 years			
Energy Star®	Yes			
Case Qty	6 Inner / 24 Master			